


CKC

LIGHT IT LIKE IT



ZB7X IP



Adopts 7 × 60W RGBW LED light source
 Total luminous flux 5,100 lumens
 Beam Angle 4° ~54° zoom
 CCT 2700 ~ 10000K
 IP65 rating, resistant to harsh environments such as rain, dust, and extreme temperatures, suitable for both indoor and outdoor applications

OPTAL

- Source: 7 × 60W RGBW LED
- Output: 5100 Lm
- Beam angle: 4 ~ 38°
- Field angle: 6 ~ 54°
- CCT: 2700 ~ 10000K
- Source lifetime: 20000 H

EFFECT

- Strobe: 1~25Hz
- Uniform RGBW color mixing system and rainbow effect, single point LED control
- Create unlimited dynamic, unlimited color changes

CONTROL & PROGRAM

- Channel: 17/21/45 CH
- Protocol: DMX512, RDM, ArtNet/sACN
- Data connector: 3PIN XLR, RJ45 In/Out
- Display: 1.8 inches touch screen, the operation panel has a rechargeable battery that allows you to access the menu to set the address code and make other settings without power on

SOFTWARE

- Via DMX signal to update
- Static waterproof fan, intelligent speed control
- Intelligent temperature protection to ensure LED service life

PAN & TILT MOVEMENT

- Pan: 540° or 630° 8bit/16bit
- Tilt: 270° 8bit/16bit

HOUSING

- Aluminum alloy structure + plastic (VO)
- Fan cooling
- Resistant to salt corrosion

POWER CONSUMPTION

- Voltage: AC 100V~240V 50/60Hz
- Rated power: 550 W

OTHER

- IP rating: IP65
- Work environment: -40°C ~ 45°C
- Startup environment: -20°C ~ 45°C

SIZE & WEIGHT

- Size: 359 × 239 × 463 mm
- N.W: 16 kgs



PHOTOMETRICAL DATA

Distance(m)	0	8	10	15	20
Lux 4°		6650	4220	1891	1064
Diameter(m)		0.56	0.70	1.05	1.40
Lux 54°		261	179	74	
Diameter(m)		8.15	10.19	15.29	

