

LIGHT IT LIKE IT



FC Profile 200



Adopts 250W RGBAL LED
 Beam angle: 26 ~ 50°
 Output: 5825 Lm
 CCT: 2400 ~ 8500K
 CRI: 93
 Framing: Manual
 Silent fan, intelligent speed regulation

OPTIC

- Source: 250W RGBAL LED
- Beam angle: 26~50°
- Output: 5825 Lm
- CRI: 93
- CCT: 2400K~8500K
- Source lifetime: >20000 H

EFFECT

- Strobe: 1~25Hz
- Framing: Manual

CONTROL & PROGRAM

- Channel: 1 / 3 / 5 / 6 / 7 / 9 / 10 / 11 / 15 / 19 CH
- Protocol: DMX512, RDM
- Data connector: 3 PIN XLR
- Display: O LED display

SOFTWARE

- Via DMX signal to update
- Intelligent temperature protection to ensure LED service life

HOUSING

- Structure of metal injection molded parts
- Fan cooling (intelligent speed regulation)

POWER CONSUMPTION

- Voltage: AC 100V~240V 50/60Hz
- Rated power: 270 W

OTHER

- IP rating: IP30
- Work environment: -40°C ~ 45°C
- Startup environment: -20°C ~ 45°C

SIZE & WEIGHT

- Size: 264 × 472 × 394 mm
- N.W: 6.9 kgs



PHOTOMETRICAL DATA

Distance(m)	0	8	15	30
Lux 26°		5010	1940	780
Diameter(m)		1.39	2.31	3.69
Lux 50°		1830	761	336
Diameter(m)		2.80	4.66	7.46

