



LIGHT IT LIKE IT



ZB19X IP



Adopts 19 × 60W RGBW LED light source
 Total luminous flux 21,000 lumens
 Beam Angle 4° ~60° zoom
 CCT 2700 ~ 10000K
 IP65 rating, resistant to harsh environments such as rain, dust, and extreme temperatures, suitable for both indoor and outdoor applications

OPTIC

- Source: 19 × 60W RGBW LED
- Output: 21000 Lm
- Beam angle: 4 ~ 60°
- CCT: 2700 ~ 10000K
- Source lifetime: >20000 H

EFFECT

- Strobe: 1~25Hz
- Uniform RGBW color mixing system and rainbow effect, single point LED control
- Create unlimited dynamic, unlimited color changes

CONTROL & PROGRAM

- Channel: 17/21/93 CH
- Protocol: DMX512, RDM, ArtNet/sACN
- Data connector: 3PIN XLR, RJ45 In/Out
- Display: 1.8 inches touch screen, the operation panel has a rechargeable battery that allows you to access the menu to set the address code and make other settings without power on

SOFTWARE

- Via DMX signal to update
- Static waterproof fan, intelligent speed control
- Intelligent temperature protection to ensure LED service life

PAN & TILT MOVEMENT

- Pan: 540° or 630° 8bit/16bit
- Tilt: 270° 8bit/16bit

HOUSING

- Aluminum alloy structure + plastic (VO)
- Fan cooling
- Resistant to salt corrosion

POWER CONSUMPTION


- Voltage: AC 100V~240V 50/60Hz
- Rated power: 1450 W
- Power factor: 0.99

OTHER

- IP rating: IP65
- Work environment: -40°C ~ 45°C
- Startup environment: -20°C ~ 45°C

SIZE & WEIGHT

- Size: 433 × 310 × 545 mm
- N.W: 26.3 kgs



PHOTOMETRIC DATA

Distance(m)	0	8	12	15	20
Lux 4°		22500	9970	6400	3600
Diameter(m)		0.56	0.84	1.05	1.40
Lux 60°		953	565	271	152
Diameter(m)		9.24	13.86	17.32	23.09