

# ZB7X IP 77\*60W/ RGBW LED OUTPUT BEAM ANGLE 2700 17/21/45 CHANNEL DMX 540°270° PAN/TILT 550W IP65

Adopts 7 × 60W RGBW LED light source Total luminous flux 5,700 lumens Ream Angle 4° ~54° zoom

Beam Angle 4° ~54° zoom CCT 2700 ~ 10000K

Uniform RGBW color mixing system and rainbow effect

Rich color mixing effect, linear adjustable color temperature

IP65 rating, resistant to harsh environments such as rain, dust, and extreme temperatures, suitable for both indoor and outdoor applications

### OPTIC

- Source: 7 × 60W RGBW LED(OSRAM)

- Output: 5700 Lm - Zoom Range: 4~54° - CCT: 2700~10000 K - Source lifetime: >20000 H

### EFFECT

- Strobe: 1 ~ 25Hz

- Uniform RGBW color mixing system and rainbow effect, single point LED control

- Create unlimited dynamic, unlimited color changes

# CONTROL & PROGRAM

Channel: 17/21/45 CHProtocal: DMX512, RDMData connector: 3 PIN XLR

- Display: 1.8 LCD screen the operation panel has a rechargeable battery that allows you to access the menu to set the address code and make other settings without power on

### SOFTWARE

- Via USB & DMX signal to update

- Silent fan, intelligent speed regulation

- Intelligent temperature protection to ensure LED service life

### PAN & TILT MOVEMENT

- Pan: 540° or 630° 8bit/16bit

- Tilt: 270° 8bit/16bit

# HOUSING

- Aluminum alloy structure + plastic (VO)

- Fan cooling

- Resistant to salt corrosion

### POWER CONSUMPTION

- Voltage: AC 100V~240V 50/60Hz

- Rated power: 550 W - Power factor: 0.99

# OTHER

- IP rating: IP65

Work environment: -40°C ~ 45°CStartup environment: -20°C ~ 45°C

## SIZE & WEIGHT

- Size:  $358 \times 239 \times 465 \, \text{mm}$ 

- N.W: 16 kgs







