

LIGHT KIT



Profile 300

 300W WW LED	 5°/10°/14° 18°/25°/30° 30°/35°/50° BEAM ANGLE	 3200 K CCT	 9000Lm OUTPUT	 Ra95+ CRI	 FRAMING BLADES
 1/3/4 CHANNEL	 512 DMX	 RDM	 262W		

Adopts 300W WW LED

Beam angle: 5° /10° /14° /19° /26° /36° /50° /15 ~ 30° /25 ~ 50° (Optional)

CCT: 3200K/4500K/5600K(Optional)

CRI: 95

Output: 9000 Lm

Framing: Manual

OPTIC

- Source: 300W WW LED

- Beam angle: 5° /10° /14° /19° /26° /36° /50° /15 ~ 30° /25 ~ 50° (Optional)

- CCT: 3200K/4500K/5600K(Optional)

- CRI: 95

- Output: 9000 Lm

- Source lifetime: >20000 H

EFFECT

- Strobe: 1 ~ 25Hz

- Framing: Manual

- DimCurve: 4 kinds

CONTROL & PROGRAM

- Channel: 1 / 3 / 4 CH

- Protocol: DMX512, RDM

- Data connector: 3 PIN XLR

- Display: OLED display

SOFTWARE

- Via DMX signal to update

- Silent fan, intelligent speed regulation

- Intelligent temperature protection to ensure LED service life

HOUSING

- Structure of metal injection molded parts

- Fan cooling

POWER CONSUMPTION

- Voltage: AC 100V ~ 240V 50/60Hz

- Rated power: 262 W

OTHER

- IP rating: IP30

- Work environment: -40°C ~ 45°C

- Startup environment: -20°C ~ 45°C

SIZE & WEIGHT

- Size: 683 × 302 × 456 mm

- N.W: 9.1 kgs



PHOTOMETRICAL DATA

Distance(m)	0	3	5	8	12
5°/10°/14° /19°/26°/ 36°/50° CRI: 95					
Lux 5°					3828
Diameter(m)					1.05
Lux 10°					2496
Diameter(m)					2.10
Lux 14°		16390	5922	2424	
Diameter(m)		0.74	1.23	1.96	
Lux 19°		10300	3899	1627	
Diameter(m)		1.00	1.67	2.68	
Lux 26°		8895	3106	1352	
Diameter(m)		1.39	2.31	3.69	
Lux 36°		4691	1790	756	
Diameter(m)		1.95	3.25	5.20	
Lux 50°		2592	943	423	
Diameter(m)		2.80	4.66	7.46	

