

LIGHT KIT



FC Halonel Plus



Adopts 500W RGBAL LED
 Total luminous flux 17400 Lm
 Zoom Range: 8~60°
 CCT: 2400~8500K
 Ra/97, R9/97
 IP66

OPTIC

- Source: 500W RGBAL LED
- Output: 17400 Lm
- Zoom range: 8~60°
- CCT: 2400K ~ 8500K
- CRI: 97
- R9: 97
- Source lifetime: >20000 H

EFFECT

- Strobe: 1 ~ 25Hz
- Dimmer Curve: 4 kinds

CONTROL & PROGRAM

- Channel: 1 / 5 / 7 / 11 / 12 / 20 / 10 / 16 / 14 CH
- Protocol: DMX512, RDM
- Data connector: 3 PIN (or 5 PIN) XLR
- Display: OLED display

SOFTWARE

- Via DMX signal to update
- Intelligent temperature protection to ensure LED service life

HOUSING

- Aluminum alloy structure
- Fan cooling

POWER CONSUMPTION


- Voltage: AC 100V~240V 50/60Hz
- Rated power: 562 W

OTHER

- IP rating: IP66
- Work environment: -40°C ~ 45°C
- Startup environment: -20°C ~ 45°C

SIZE & WEIGHT

- Size: 302 × 448 × 538 mm
- N.W: 13 kgs



PHOTOMETRICAL DATA

Distance(m)	0	3	5	8
Lux 8°		55K	21.6K	8620
Diameter(m)		0.42	0.70	1.12
Lux 60°		4740	1830	824
Diameter(m)		3.46	5.77	9.24