


CKC

LIGHT
TWEET



EvoT Double



Adopts 16 × 60W RGBL LED + 32×10W CW LED light source
 Total luminous flux 24,000 lumens
 Beam Angle 3~54° zoom
 CCT 2400 ~ 8500K
 IP55

OPTIC

- Source: 16 × 60W RGBL LED + 32×10W CW LED
- Output: 24000 Lm
- Zoom Range: 3~54°
- CCT: 2400 ~ 8500K
- Source lifetime: >20000 H

EFFECT

- Strobe: 1~25Hz
- LED refresh rate: 1200Hz~25KHz
- Uniform RGBL color mixing system and rainbow effect, single point LED control
- Create unlimited dynamic, unlimited color changes

CONTROL & PROGRAM

- Channel: 24/33/121CH
- Protocol: DMX512, RDM, ArtNet/sACN
- Data connector: 3 PIN (or 5 PIN) XLR,RJ45
- Display: 2.4 inches screen
- NFC: The lighting fixtures do not require power on and can be directly set up, diagnosed, and perform other functions through the CKC app

SOFTWARE

- Via DMX signal to update
- Static waterproof fan, intelligent speed control
- Intelligent temperature protection to ensure LED service life

TILT MOVEMENT

- Tilt: 210° 8bit/16bit

HOUSING

- Aluminum alloy structure + plastic (VO)
- Fan cooling

POWER CONSUMPTION

- Voltage: AC 100V~240V 50/60Hz
- Rated power: 1300 W

OTHER


- IP rating: IP55
- Work environment: -40°C ~ 45°C
- Startup environment: -20°C ~ 45°C

SIZE & WEIGHT

- Size: 1004 × 140 × 337 mm
- N.W: 24.7 kgs



PHOTOMETRIC DATA

Distance(m)	0	5	10	15	30	50
						
Lux 3°		25700	10300	6670	450	162
Diameter(m)		0.26	0.52	0.79	1.57	2.62
Lux 54°		2560	624	288	160	26
Diameter(m)		5.10	10.19	15.29	20.38	50.95

